

DH470

FORM FACTOR	1.3L chassis
PROCESSOR	Support Cometlake-s LGA1200 socket Core i3/i5/i7/i9, Pentium, Celeron 65W processor
CHIPSET	Intel H470 Express chipset
MEMORY	2 x DDR4 SODIMM slots,32GB per DIMM (Max 64GB) DDR4 2666/2933 MHz
VIDEO OUTPUT	HDMI 2.0 x 1+ DisplayPort x 2, Triple video outputs 4K playback (Dual channel memory recommended) Integrated in CPU
AUDIO	Realtek ALC662 High Definition Audio
ETHERNET	Intel I210AT*2 Dual Lan 10Mb/s,100Mb/s,1Gb/s operation Support Wake-On-LAN function Support Teaming function
STORAGE INTERFACE	SATA 6.0Gb/s interface
ONBOARD CONNECTORS	(1) 4pin fan connector (1) VGA(For PVG01 use) (1) 1x4 pin USB header(For WWN03 use) (1) SATA connector w/power (1) Front audio header (1) Auto power on header (1) RS232 voltage switch
FRONT PANEL	(2) USB 3.2 Gen1 ports (Include Type C x1) (2) USB 3.2 Gen2 ports (1) Microphone-In (1) Earphone-Out (1) Power-On button (1) Power LED (1) HDD LED (1) SD Card reader
BACK PANEL	(2) RJ45 Gigabit LAN port w/LED (1) HDMI port (2) Display port (2) USB 3.2 Gen1 ports (2) USB 3.2 Gen2 ports (1) RS232 (1) RS232/RS422/RS485 (1) External 4pin header (1) DC-in (2) Wireless Antenna fixture (1) Kensington lock
DRIVE BAYS	(1) 2.5" HDD / SSD bay

DIMENSIONS	190(L) x 165(W) x 43(H) mm
POWER	90W Power Adapter Input:100- 240V AC 19V 4.74A DC
ACCESSORIES	XPC Multilanguage Quick User Guide XPC DVD Driver VESA mount VESA Screw pack Power cord Thermal Grease HDD Screw pack 90W adapter
EXPANSION SLOT	(1) M.2 2280 Type M key socket (1) M.2 2230 Type E key socket
OS SUPPORT	Windows 10 64 bit O.S Linux
REMARK	RS232 ports support 0/5/12V output. Voltage setting please refer to Quick Guide.