

DH410

FORM FACTOR	1.3L chassis
PROCESSOR	Support Cometlake-s LGA1200 socket Core i3/i5/i7/i9, Pentium, Celeron 65W processor
CHIPSET	Intel H410 Express chipset
MEMORY	2 x DDR4 SODIMM slots,32GB per DIMM (Max 64GB) DDR4 2666/2933 MHz
VIDEO OUTPUT	HDMI 2.0 + DisplayPort, Dual video output 4K playback (Dual channel memory recommended) Integrated in CPU
AUDIO	Realtek ALC662 High Definition Audio
ETHERNET	Intel I210AT*2 Dual Lan 10Mb/s,100Mb/s,1Gb/s operation Support Wake-On-LAN function Support Teaming function
STORAGE INTERFACE	SATA 6.0Gb/s interface
ONBOARD CONNECTORS	(1) 4pin fan connector (1) VGA(For PVG01 use) (1) 1x4 pin USB header(For WWN03 use) (1) SATA connector w/power (1) Front audio header (1) Auto power on header (1) RS232 voltage switch
FRONT PANEL	(2) USB 2.0 ports (2) USB 3.2 Gen1 ports (1) Microphone-In (1) Earphone-Out (1) Power-On button (1) Power LED (1) HDD LED (1) SD Card reader
BACK PANEL	(2) RJ45 Gigabit LAN port w/LED (Green-link/Yellow-active) (1) HDMI port (1) Display port (2) USB 2.0 ports (2) USB 3.2 Gen1 ports (1) RS232 (1) RS232/RS422/RS485 (1) External 4pin header (1) DC-in (2) Wireless Antenna fixture (1) Kensington lock
DRIVE BAYS	(1) 2.5" HDD / SSD bay

DIMENSIONS	190(L) x 165(W) x 43(H) mm
POWER	90W Power Adapter Input:100- 240V AC 19V 4.74A DC or Output:12V/7.5A DC
ACCESSORIES	XPC Multilanguage Quick User Guide XPC DVD Driver VESA mount VESA Screw pack Power cord Thermal Grease HDD Screw pack 90W adapter
EXPANSION SLOT	(1) M.2 2280 Type M key socket (1) M.2 2230 Type E key socket
OS SUPPORT	Windows 10 64 bit O.S Linux
REMARK	RS232 ports support 0/5/12V output. Voltage setting please refer to Quick Guide.